

Akustikabsorber

FAI



Aluminium facing with fibreglass support and M-1 class fire-resistant absorbing polyurethane foam.

Measurements according to UNE-EN ISO 140-3 standard (December 1995) Acoustic Isolation of Construction Materials in Laboratory Measurements. Corresponds completely with ISO 140-3(1995) standard. Cancels and substitutes UNE 74-040/3 (1984) standard. Calculations according to NBCEA88.

Tipo	Codice	autoadesive	Rw (dB)	Peso (kg.)
FAI-15 plancha	26251	-	19	1,335
FAI-15 A plancha	26253	x	19	1,335
FAI-25 plancha	26252	-	23	2,085
FAI-25 A plancha	26254	x	23	2,085

CARATTERISTICHE TECNICHE

— Composition

Aluminium facing with fibreglass support and M-1 class fire-resistant absorbing polyurethane foam.

— Thicknesses

15mm 25mm

FORMATS

— Sheets

1200x1000 mm
15mm thick, 8 Sheets per box.
25mm thick, 5 Sheets per box.

— Rolls

Consult for roll manufacturing.

APPLICAZIONI

Aislante térmico, comportamiento M-1 ignífugo, buena resistencia al empape de hidrocarburos y no muy buen absorbente acústico pero sí buen aislante.

Akustikabsorber **FAI**

PROPRIETÀ ACUSTICHE

