

# Akustikabsorber

## PAIM



Aluminium facing with fiberglass support, absorbing polyurethane foam and 5 Kg/m<sup>2</sup> heavy viscoelastic mass.

Measurements according to UNE-EN ISO 140-3 standard (December 1995) Acoustic Isolation of Construction Materials in Laboratory Measurements. Corresponds completely with ISO 140-3(1995) standard. Cancels and substitutes UNE 74-040/3 (1984) standard. Calculations according to NBCEA88.

Tipo	Codice	autoadesive	Rw (dB)	Peso (kg.)
PAIM-15 plancha	26122	-	20	6,853
PAIM-15 A plancha	26116	x	20	6,853
PAIM-25 plancha	26123	-	21	7,155
PAIM-25 A plancha	26117	x	21	7,155
PAIM-40 plancha	26124	-	22	7,608
PAIM-40 A plancha	26118	x	22	7,608

### CARATTERISTICHE TECNICHE

#### — Composition

Aluminium facing with fiberglass support, absorbing polyurethane foam and 5 Kg/m<sup>2</sup> heavy viscoelastic mass.

#### — Thicknesses

15mm 25mm 40mm

### FORMATS

#### — Sheets

1200x1000 mm  
15mm thick, 8 Sheets per box.  
25mm thick, 5 Sheets per box.  
40mm thick, 3 Sheets per box.

### APPLICAZIONI

Aislante térmico, comportamiento M-1 ignífugo, buena resistencia al empape de hidrocarburos y no muy buen absorbente acústico pero sí buen aislante y lámina amortiguante que aumenta la masa y amortigua las vibraciones.

# Akustikabsorber

## PAIM

### PROPRIETÀ ACUSTICHE

