

Akustikabsorber

PFM



Black unwoven film, absorbing polyurethane foam and 5 Kg/m² heavy viscoelastic mass.

Measurements according to UNE-EN ISO 140-3 standard (December 1995) Acoustic Isolation of Construction Materials in Laboratory Measurements. Corresponds completely with ISO 140-3(1995) standard. Cancels and substitutes UNE 74-040/3 (1984) standard. Calculations according to NBCEA88.

Tipo	Codice	autoadesive	Rw (dB)	Peso (kg.)
PFM-15 plancha	26135	-	14	7,113
PFM-15 A plancha	26138	x	14	7,113
PFM-25 plancha	26136	-	14	7,415
PFM-25 A plancha	26139	x	14	7,415
PFM-40 plancha	26137	-	14	7,868
PFM-40 A plancha	26140	x	14	7,868

CARATTERISTICHE TECNICHE

— Composition

Black unwoven film, absorbing polyurethane foam and 5 Kg/m² heavy viscoelastic mass.

— Thicknesses

15mm 25mm 40mm

FORMATS

— Sheets

1200x1000 mm
15mm thick, 8 Sheets per box.
25mm thick, 5 Sheets per box.
40mm thick, 3 Sheets per box.

APPLICAZIONI

Revestimiento interior de cabinas insonorizadas o de vehículos, buena absorción y lámina amortiguante que aumenta la masa y amortigua las vibraciones.

Akustikabsorber

PFM

PROPRIETÀ ACUSTICHE

