

Akustikabsorber

PIM



Fiberglass facing and absorbing polyurethane foam and 5 Kg/m² heavy viscoelastic mass.

Measurements according to UNE-EN ISO 140-3 standard (December 1995) Acoustic Isolation of Construction Materials in Laboratory Measurements. Corresponds completely with ISO 140-3(1995) standard. Cancels and substitutes UNE 74-040/3 (1984) standard. Calculations according to NBCEA88.

Tipo	Codice	autoadesive	Rw (dB)	Peso (kg.)
PIM-15 plancha	26119	-	19	6,663
PIM-15 A plancha	26113	x	19	6,663
PIM-25 plancha	26120	-	19	6,965
PIM-25 A plancha	26114	x	19	6,965
PIM-40 plancha	26121	-	21	7,418
PIM-40 A plancha	26115	x	21	7,418

CARATTERISTICHE TECNICHE

— Composition

Fiberglass facing and absorbing polyurethane foam and 5 Kg/m² heavy viscoelastic mass.

— Thicknesses

15mm 25mm 40mm

FORMATS

— Sheets

1200x1000 mm
15mm thick, 8 Sheets per box.
25mm thick, 5 Sheets per box.
40mm thick, 3 Sheets per box.

APPLICAZIONI

Aislante térmico, buena resistencia al empape de hidrocarburos y no muy buen absorbente acústico pero sí buen aislante y lámina amortiguante que aumenta la masa y amortigua las vibraciones.

Akustikabsorber

PIM

PROPRIETÀ ACUSTICHE

