

## Akustikabsorber

### PSM



Black PU film, absorbing polyurethane foam and 5 Kg/m<sup>2</sup> heavy viscoelastic mass.

Measurements according to UNE-EN ISO 140-3 standard (December 1995) Acoustic Isolation of Construction Materials in Laboratory Measurements. Corresponds completely with ISO 140-3(1995) standard. Cancels and substitutes UNE 74-040/3 (1984) standard. Calculations according to NBCEA88.

Tipo	Codice	autoadesive	Rw (dB)	Peso (kg.)
PSM-15 plancha	26107	-	14	6,463
PSM-15 A plancha	26101	x	14	6,463
PSM-25 plancha	26109	-	17	6,765
PSM-25 A plancha	26103	x	17	6,765
PSM-40 plancha	26111	-	20	7,218
PSM-40 A plancha	26105	x	20	7,218

#### CARATTERISTICHE TECNICHE

##### — Composition

Black PU film, absorbing polyurethane foam and 5 Kg/m<sup>2</sup> heavy viscoelastic mass.

##### — Thicknesses

15mm 25mm 40mm

#### FORMATS

##### — Sheets

1200x1000 mm  
15mm thick, 8 Sheets per box.  
25mm thick, 5 Sheets per box.  
40mm thick, 3 Sheets per box.

#### APPLICAZIONI

Revestimiento absorbente de cabinas insonorizadas o de vehículos donde exista un peligro de empape de hidrocarburos o agua del material absorbente y lámina amortiguante que aumenta la masa y amortigua las vibraciones.

# Akustikabsorber

## PSM

### PROPRIETÀ ACUSTICHE

