

# Akustikabsorber

## PS WHITE

White PU film and absorbing polyurethane foam.



Measurements according to UNE-EN ISO 140-3 standard (December 1995) Acoustic Isolation of Construction Materials in Laboratory Measurements. Corresponds completely with ISO 140-3(1995) standard. Cancels and substitutes UNE 74-040/3 (1984) standard. Calculations according to NBECA88.

Tipo	Codice	autoadesive	Rw (dB)	Peso (kg)
PS-15 plancha	26002	-	12	0,463
PS-15 A plancha	26092	x	12	0,463
PS-15 rollo	26058	-	12	0,503
PS-15 A rollo	26095	x	12	0,503
PS-25 plancha	26005	-	12	0,765
PS-25 A plancha	26093	x	12	0,765
PS-25 rollo	26059	-	12	0,805
PS-25 A rollo	26096	x	12	0,765
PS-40 plancha	26008	-	17	1,218
PS-40 A plancha	26094	x	17	1,218
PS-40 rollo	26060	-	17	1,258
PS-40 A rollo	26097	x	17	1,218

### CARATTERISTICHE TECNICHE

#### — Composition

White PU film and absorbing polyurethane foam.

#### — Thicknesses

15mm 25mm 40mm

### FORMATS

#### — Sheets

1200x1000 mm  
15mm thick, 8 Sheets per box.  
25mm thick, 5 Sheets per box.  
40mm thick, 3 Sheets per box.

#### — Rolls

15mm thick, 1500mm wide x approx. 20m long  
25mm thick, 1500mm wide x approx. 20m long  
40mm thick, 1500mm wide x approx. 15m long

### APPLICAZIONI

Revestimiento absorbente de cabinas insonorizadas o de vehículos donde exista un peligro de empape de hidrocarburos o agua del material absorbente.

# Akustikabsorber

## PS WHITE

### PROPRIETÀ ACUSTICHE

