

Akustikabsorber

PF BLACK



Black unwoven fabric and absorbing polyurethane foam.

Measurements according to UNE-EN ISO 140-3 standard (December 1995) Acoustic Isolation of Construction Materials in Laboratory Measurements. Corresponds completely with ISO 140-3(1995) standard. Cancels and substitutes UNE 74-040/3 (1984) standard. Calculations according to NBECA88.

Tipo	Codice	autoadesive	Rw (dB)	Peso (kg.)
PF-15 rollo	26160	-	11	0,463
PF-15 A rollo	26163	x	11	0,49
PF-25 rollo	26161	-	12	0,765
PF-25 A rollo	26164	x	12	0,81
PF-40 rollo	26162	-	11	1,218
PF-40 A rollo	26165	x	11	1,218
PF-15 A sheet	26291	x	11	0,463
PF-25 A sheet	26292	x	12	0,715
PF-40 A sheet	26193	x	11	1,218
PF-15 sheet	26166	-	11	0,463
PF-25 sheet	26167	-	12	0,715
PF-40 sheet	26168	-	11	1,218

CARATTERISTICHE TECNICHE

— Composition

Black unwoven fabric and absorbing polyurethane foam.

— Thicknesses

15mm 25mm 40mm

FORMATS

— Sheets

1200x1000 mm
15mm thick, 8 Sheets per box.
25mm thick, 5 Sheets per box.
40mm thick, 3 Sheets per box.

— Rolls

1500mm wide x approx. 20m long

APPLICAZIONI

Revestimiento interior de cabinas insonorizadas o de vehículos, buena absorción.

Akustikabsorber

PF BLACK

PROPRIETÀ ACUSTICHE

