

SCH WASHER



The AMC-Mecanocaucho® SCH type anti vibration mounts are made of two moulded parts . One of circular fully moulded rubber, and one circular part which is fully bonded to a centre tube which acts as a guide for the machine anchoring bolt. They are installed pre-compressed on the actual machine frame, whose thickness "E" determines the degree of pre-compression of the assembly.

TECHNICAL CHARACTERISTICS

Washers should be used, if the rubber surface is not covered with the contact surface

APPLICATIONS

- Vehicle cabins
- Public works and agricultural vehicles, etc.



DIMENSIONS

Type	Weight (kg)	Øext (mm)	Øint (mm)	THICKNESS (mm)	Code
SCH 35 WASHER	0,03	38	8,5	2	610053
SCH 50 WASHER	0,051	54	12,5	3	611080
SCH 65 WASHER	0,125	67	16,5	5	606130
SCH 90 WASHER	0,31	95	22	6	608101
SCH 125 WASHER	0,58	125	25	8	610123

OPERATION AND ASSEMBLY



The SCH mounts should be assembled according to the following installation instructions. There are two possible configurations, see previous assembly picture. They can be installed in plates of different thicknesses according to the T_{mx} and T_{min} values given in the Table provided . The load vs deformation curves will vary according to the plate thickness in which the mount will be installed.

Washers should be used, if the rubber surface is not covered with the contact surface.