

# CB WASHER



AMC-MECANOCAUCHO® type CB anti vibration mounts are installed in pairs. Installation is simplified as both mounts are fixed with one through bolt and washers at each end of the installed mount .

The CB mount is provided with a built in radial wear plate that prevents the elastomeric element coming into contact with the sharp edges of laser cut holes in support frames or structures that can cause friction in traditionally used semi-bonded mounts . This wear plate reduces the need to machine radii or chamfer holes , reducing cost. The specific design permits high dynamic loading whilst limiting movement due to their multi-axial snubbing .

## TECHNICAL CHARACTERISTICS

Washers should be used, if the rubber surface is not covered with the contact surface

## APPLICATIONS

- Agricultural or construction equipment cabins, engines, radiators, transmission ,battery boxes.
- Marine equipment
- Mobile Generators or compressors.
- Chassis frames for Military, Bus, Truck, Motorhome and Emergency vehicles.



## DIMENSIONS

Type	Weight (gr)	Øext (mm)	Øint (mm)	THICKNESS (mm)	Code
CB 40 WASHER	16	38	8,5	2	610053
CB 60 WASHER	125	66	16,5	5	606130
CB 65 WASHER	141	67	18,5	5	706004
CB 76 WASHER	175	76	16,5	5	608074
CB 80 WASHER	175	76	16,5	5	608074
CB 110 WASHER	286	110	23	5	610192
CB 130 WASHER	1251	145	30,5	10	608278
CB 150 WASHER	1251	145	30,5	10	608278

ADVANTAGES



**MECANOCAUCHO**

The specific design of the mounts permits high dynamic loads whilst limiting the movement due to the multiple axial snubbing design.



**AMC MECANOCAUCHO**  
Industrialdea Zona A - Pab. 35.  
Asteasu E-20159, Gipuzkoa  
Spain



Tel.: +34 943 69 61 02  
Fax: +34 943 69 62 19



sales@amcsa.es



www.mecanocaucho.com  
www.akustik.com