

Akustikabsorber

PFM



Black unwoven film, absorbing polyurethane foam and 5 Kg/m² heavy viscoelastic mass.

Measurements according to UNE-EN ISO 140-3 standard (December 1995) Acoustic Isolation of Construction Materials in Laboratory Measurements. Corresponds completely with ISO 140-3(1995) standard. Cancels and substitutes UNE 74-040/3 (1984) standard. Calculations according to NBECA88.

Type	Code	SELF-ADHESIVE	Rw (dB)	Weight (kg.)
PFM-15 sheet	26135	-	14	7,113
PFM-15 A sheet	26138	x	14	7,113
PFM-25 sheet	26136	-	14	7,415
PFM-25 A sheet	26139	x	14	7,415
PFM-40 sheet	26137	-	14	7,868
PFM-40 A sheet	26140	x	14	7,868

TECHNICAL CHARACTERISTICS

— Composition

Black unwoven film, absorbing polyurethane foam and 5 Kg/m² heavy viscoelastic mass.

— Thicknesses

15mm 25mm 40mm

FORMATS

— Sheets

1200x1000 mm
15mm thick, 8 Sheets per box.
25mm thick, 5 Sheets per box.
40mm thick, 3 Sheets per box.

APPLICATIONS

Lining interior of soundproof cabins and vehicles, good absorption, and damping sheet that increases the mass and dampens vibrations.

Akustikabsorber

PFM

ACOUSTIC PROPERTIES

