

Akustikabsorber

FAR



Black unwoven film and M-1 class fire-resistant absorbing polyurethane foam.

Measurements according to UNE-EN ISO 140-3 standard (December 1995) Acoustic Isolation of Construction Materials in Laboratory Measurements. Corresponds completely with ISO 140-3(1995) standard. Cancels and substitutes UNE 74-040/3 (1984) standard. Calculations according to NBCEA88.

| Typ | Art.Nr. | Selbstklebend | Rw (dB) | Gewicht (kg.) |
|-----------------|---------|---------------|---------|---------------|
| FAR-15 Platte | 26241 | - | 10 | 1,335 |
| FAR-15 A Platte | 26242 | x | 10 | 1,335 |
| FAR-25 Platte | 26243 | - | 10 | 2,085 |
| FAR-25 A Platte | 26244 | x | 10 | 2,085 |

TECHNISCHE MERKMALE

— Composition

Black unwoven film and M-1 class fire-resistant absorbing polyurethane foam.

— Thicknesses

15mm 25mm

FORMAT

— Platten

1200x1000 mm
15mm stark, 8 Platten pro Karton.
25mm stark, 5 Platten pro Karton.

— Rolle

Consult for roll manufacturing.

ANWENDUNGEN

Revestimiento interior de cabinas insonorizadas o de vehículos, buena absorción y absorbente con comportamiento ignífugo M-1.

Akustikabsorber **FAR**

AKUSTISCHE EIGENSCHAFTEN

