

Akustikabsorber

PSM



Black PU film, absorbing polyurethane foam and 5 Kg/m² heavy viscoelastic mass.

Measurements according to UNE-EN ISO 140-3 standard (December 1995) Acoustic Isolation of Construction Materials in Laboratory Measurements. Corresponds completely with ISO 140-3(1995) standard. Cancels and substitutes UNE 74-040/3 (1984) standard. Calculations according to NBCEA88.

Typ	Art.Nr.	Selbstklebend	Rw (dB)	Gewicht (kg.)
PSM-15 Platte	26107	-	14	6,463
PSM-15 A Platte	26101	x	14	6,463
PSM-25 Platte	26109	-	17	6,765
PSM-25 A Platte	26103	x	17	6,765
PSM-40 Platte	26111	-	20	7,218
PSM-40 A Platte	26105	x	20	7,218

TECHNISCHE MERKMALE

— Composition

Black PU film, absorbing polyurethane foam and 5 Kg/m² heavy viscoelastic mass.

— Thicknesses

15mm 25mm 40mm

FORMAT

— Platten

1200x1000 mm
15mm stark, 8 Platten pro Karton.
25mm stark, 5 Platten pro Karton.
40mm stark, 3 Platten pro Karton.

ANWENDUNGEN

Revestimiento absorbente de cabinas insonorizadas o de vehículos donde exista un peligro de empape de hidrocarburos o agua del material absorbente y lámina amortiguante que aumenta la masa y amortigua las vibraciones.

Akustikabsorber

PSM

AKUSTISCHE EIGENSCHAFTEN

