

Akustikabsorber

PF SCHWARZ



Black unwoven fabric and absorbing polyurethane foam.

Measurements according to UNE-EN ISO 140-3 standard (December 1995) Acoustic Isolation of Construction Materials in Laboratory Measurements. Corresponds completely with ISO 140-3(1995) standard. Cancels and substitutes UNE 74-040/3 (1984) standard. Calculations according to NBCEA88.

Typ	Art.Nr.	Selbstklebend	Rw (dB)	Gewicht (kg.)
PF-15 Rolle	26160	-	11	0,463
PF-15 A Rolle	26163	x	11	0,49
PF-25 Rolle	26161	-	12	0,765
PF-25 A Rolle	26164	x	12	0,81
PF-40 Rolle	26162	-	11	1,218
PF-40 A Rolle	26165	x	11	1,218
PF-15 A sheet	26291	x	11	0,463
PF-25 A sheet	26292	x	12	0,715
PF-40 A sheet	26193	x	11	1,218
PF-15 sheet	26166	-	11	0,463
PF-25 sheet	26167	-	12	0,715
PF-40 sheet	26168	-	11	1,218

TECHNISCHE MERKMALE

- **Composition**
Black unwoven fabric and absorbing polyurethane foam.
- **Thicknesses**
15mm 25mm 40mm

FORMAT

- **Platten**
1200x1000 mm
15mm stark, 8 Platten pro Karton.
25mm stark, 5 Platten pro Karton.
40mm stark, 3 Platten pro Karton.
- **Rolle**
1500mm breit x ca. 20m lang

ANWENDUNGEN

Revestimiento interior de cabinas insonorizadas o de vehículos, buena absorción.

Akustikabsorber PF SCHWARZ

AKUSTISCHE EIGENSCHAFTEN

