

Akustikabsorber

FAR



Black unwoven film and M-1 class fire-resistant absorbing polyurethane foam.

Measurements according to UNE-EN ISO 140-3 standard (December 1995) Acoustic Isolation of Construction Materials in Laboratory Measurements. Corresponds completely with ISO 140-3(1995) standard. Cancels and substitutes UNE 74-040/3 (1984) standard. Calculations according to NBCEA88.

| Tipo | Codice | autoadesive | Rw (dB) | Peso (kg.) |
|------------------|--------|-------------|---------|------------|
| FAR-15 plancha | 26241 | - | 10 | 1,335 |
| FAR-15 A plancha | 26242 | x | 10 | 1,335 |
| FAR-25 plancha | 26243 | - | 10 | 2,085 |
| FAR-25 A plancha | 26244 | x | 10 | 2,085 |

CARATTERISTICHE TECNICHE

— Composition

Black unwoven film and M-1 class fire-resistant absorbing polyurethane foam.

— Thicknesses

15mm 25mm

FORMATS

— Sheets

1200x1000 mm
15mm thick, 8 Sheets per box.
25mm thick, 5 Sheets per box.

— Rolls

Consult for roll manufacturing.

APPLICAZIONI

Revestimiento interior de cabinas insonorizadas o de vehículos, buena absorción y absorbente con comportamiento ignífugo M-1.

Akustikabsorber

FAR

PROPRIETÀ ACUSTICHE

