

# Akustikabsorber

## FI



Fiberglass facing and M-1 class fire-resistant absorbing polyurethane foam.

Measurements according to UNE-EN ISO 140-3 standard (December 1995) Acoustic Isolation of Construction Materials in Laboratory Measurements. Corresponds completely with ISO 140-3(1995) standard. Cancels and substitutes UNE 74-040/3 (1984) standard. Calculations according to NBCEA88.

Tipo	Codice	autoadesive	Rw (dB)	Peso (kg.)
FI-15 plancha	26206	-	22	1,335
FI-15 A plancha	26201	x	22	1,335
FI-25 plancha	26207	-	23	2,085
FI-25 A plancha	26205	x	23	2,085

### CARATTERISTICHE TECNICHE

#### — Composition

Fiberglass facing and M-1 class fire-resistant absorbing polyurethane foam.

#### — Thicknesses

15mm 25mm

### FORMATS

#### — Sheets

1200x1000 mm  
15mm thick, 8 Sheets per box.  
25mm thick, 5 Sheets per box.

#### — Rolls

Consult for roll manufacturing.

### APPLICAZIONI

Aislante térmico, comportamiento M-1 ignífugo, buena resistencia al empape de hidrocarburos y no muy buen absorbente acústico pero sí buen aislante.

# Akustikabsorber

## FI

### PROPRIETÀ ACUSTICHE

